

# SuperFOIL

## Insulation

### EN 13984:2013 Declaration of Performance

Identification : 001-BD-CPR-01-04-19

Version no. 2 April 2019



#### 1. Product Type:

Unique identification code of the product type:

**SuperFOIL SF60 Multi Foil Insulation**

#### 2. Type:

Type batch or serial number or any other element allowing identification of the construction product as required under article 11(4):

**Batch No. on foil**

#### 3. Intended Use:

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Thermal Radiant Vapour Barrier for Buildings**

#### 4. Name, registered trade name:

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**SuperFOIL  
Boulder Developments Ltd  
BHF  
Main Street  
Norwell  
Notts  
NG23 6JN  
United Kingdom**

#### 5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable (see 4)**

#### 6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V:

**System 3**

#### 7. Notified body (hEN):

In case of declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

**hEN13984**

Notified Body	Reg No.	Test
BRE	0832	Reaction to Fire
BTTG	0338	Water Penetration

**Performed type testing under system 3 and issued test reports**

#### 8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not applicable (see 7)**

# SuperFOIL

## Insulation

## Declaration of Performance

Identification : 001-BD-CPR-01-04-19-D

Version no. 2 April 2019



### 9. Declared Performance

Essential Characteristics	Performance	Standard	Testing Body
Thermal Resistance - Core	R 3.69	ISO 8301 : 1991 BS EN 12667 : 2001	BBA
Thermal Resistance - Roof (2 Air Gaps)	R 4.65		BBA
Thermal Resistance - Wall (2 Air Gaps)	R 5.11		BBA
Emittance	0.03	NEN EN 16012 : 2012	BDA
Thickness	115	mm	
Tensile Properties - Length *	705 / 635 N/50mm	EN 12311-1	BTTG
Tensile Properties - Width *	610 / 580 N/50mm	EN 12311-1	BTTG
Elongation - Length *	26 / 16%	EN 12311-1	BTTG
Elongation - Width *	28 / 17%	EN 12311-1	BTTG
Resistance to Tearing - Length	428	EN 12310-1	BTTG
Resistance to Tearing - Width	453	EN 12310-1	BTTG
Dimensional Stability - (Relative change @ 70°C)	0.002	DIN EN 1604 : 2007-06	Fraunhofer IBP
Flexibility at low temp - (pliability)	-40 °C	EN 1109	BTTG
Resistance to Water Penetration	W1	EN 1928:2000	BTTG
Water Vapour Transmission	Pass	EN 1931	BDA
Hydrostatic Head	Pass	BS EN 20811 : 1192	BTTG
Reaction to Fire	Class E	EN 13501-1	BRE

### 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Craig Bown, Director of Boulder Developments Ltd  
01-04-2019